## HandySCAN 3D

SILVER Series



The SILVER Series is part of the HandySCAN 3D™ lineup, the industry standard in portable metrology-grade 3D scanners. This proven and trusted patented technology captures accurate and repeatable 3D measurements of any complex surface and in any location.

The HandySCAN 3D|SILVER Series is optimized to meet the needs of technology innovators and engineering professionals looking for a powerful, accessible, and reliable way to improve product development, shorten time-to-market, and reduce development costs.





Proven and trusted solution More than 5000 users around the world Best price / performance option

Worldwide repairs and customer support

## Powerful and Intuitive Software for an Optimal User Experience

VXelements is a powerful integrated 3D software platform that works in complete synergy with the entire fleet of Creaform's 3D measuring devices. With VXelements, both 3D data acquisition as well as post-treatment and analyses occur in the same intuitive interface to guarantee an optimal user experience, seamless interaction with the device, and the shortest time to a usable mesh, 3D model, or inspection report.

Acquisition modules are included with every measurement device from Creaform. They provide real-time visualization and produce better data quality from 3D measurements, making the results user-independent and maximizing device performance. Application modules are available as add-ons to process and optimize 3D scan data for diverse applications, including creating digital twins, product development, reverse engineering, inspections, and dynamic tracking.



## **Technical Specifications**

		HandySCAN SILVER™	HandySCAN SILVER™ Elite
ACCURACY (1)		Up to 0.040 mm	Up to 0.030 mm
VOLUMETRIC ACCURACY (2) (based on part size)		0.020 mm + 0.100 mm/m	0.020 mm + 0.060 mm/m
MEASUREMENT CAPABILITIES (at a working distance of 0.3 m)	Pin	1.00 mm	
	Hole	1.50 mm	
	Step	0.030 mm	
	Wall	0.75 mm	
LIGHT SOURCE (3)		14 blue laser lines	14 blue laser lines (+ 1 extra line)
SCANNING AREA		310 x 350 mm	
PART SIZE RANGE (recommended)		0.05-4 m	
WEIGHT		0.94 kg	

- (1) Typical value for diameter measurements on a calibrated sphere artefact.
- (2) Value for sphere spacing measurement on a calibrated length artefact. Results are obtained using integrated photogrammetry with volumetric accuracy optimization.
- (3) Laser class: 2M (eye safe).



For an unparalleled experience connect with us at the nearest office located in Germany.

creaform3d.com



Authorized Distributor



Specialist i professionel 3D opmåling

info@kvejborg.dk | Tel.: 4072 1687 | www.kvejborg.dk